SERIAL NO.:

10/812,660

FILED: Page 2

March 29, 2004

AMENDMENTS TO THE CLAIMS

Please add or amend the claims to read as follows, and cancel without prejudice or

disclaimer to resubmission in a divisional or continuation application claims indicated as

cancelled:

1. (Currently Amended) A method for multicasting in a wireless network delivering

information in a wireless network, the method-comprising:

receiving from [[a]] two or more client devices-application, a request for delivery of

application data packets the information, wherein the request includes a multicast address

an address for the source of information and a quality of service attribute for receiving the

information;

checking an existence of said multicast address in a multicast schedule and updating

said multicast schedule or creating a new multicast schedule based on the existence of the

multicast address; which coordinating coordinates the multicast delivery with a power

saving protocol of each client device so that the client device will be awake when the

multicast delivery of application data packets occurs;

sending to the client application a response and coordinating said power saving

protocol to accommodate the scheduled multicast delivery of the information with the client

application; and

sending the information to application data packets to the requesting client

application device according to the multicast schedule;

receiving a request for deleting said multicast schedule from a last client device

associated with said multicast schedule; and

deleting said multicast schedule.

2. (Cancelled).

3. (Cancelled).

4. (Cancelled).

5. (Currently Amended) The method of claim 1 further comprising:

SERIAL NO.:

10/812,660

March 29, 2004

FILED: Page 3

deleting the multicast schedule after all clients the client devices associated with the

multicast schedule have been sent the information.

6. (Currently Amended) The method of claim 5 wherein deleting the multicast schedule

comprises receiving a deletion request from each client device associated with the multicast

schedule to delete the multicast schedule.

7. (Currently Amended) The method of claim 1, wherein the wireless network comprises a

wireless local area network (WLAN) complies with at least Institute of Electrical and

Electronic Engineers (IEEE) 802.11(a) and (g) standards and wherein the request comprises

a transmission specification (TSPEC) request including said multicast address and said

quality of service attribute.

8. (Previously Presented) The method of claim 1 wherein the response comprises a

transmission specification (TSPEC) response.

9. (Currently Amended) A method of receiving information in a wireless network by a

client device, the method comprising:

sending a request for delivery of the information, the request including a multicast

designation an address for the source of information and a desired quality of service

attribute for receiving the information;

receiving a response that confirms a scheduled delivery of the information to an

application layer;

coordinating a power saving protocol of said client device to accommodate the

scheduled delivery of the information to awake state based on a multicast schedule; and

receiving the information according to the scheduled delivery.

10. Cancelled.

11. Cancelled.

12. Cancelled.

SERIAL NO.: 1

10/812,660

FILED:

March 29, 2004

Page 4

13. (Currently Amended) The method of claim 9 comprising receiving the information over a wireless local area network (WLAN) complying with an at least Institute of Electrical and

Electronic Engineers (IEEE) 802.11 standards.

14. (Previously Presented) The method of claim 13 comprising receiving the information

over the WLAN uses orthogonal frequency division multiplexing (OFDM).

15. (Previously Presented) The method of claim 9 wherein sending the request comprises

sending a transmission specification (TSPEC).

16. (Previously Presented) The method of claim 9 further comprising sending a schedule

deletion request to delete from said multicast schedule.

17. (Currently Amended) A wireless communication apparatus comprising:

an application requesting media to request a multicast delivery of information;

a media access controller (MAC) operably coupled to the application requesting

media to send a request including a multicast designation an address for the source of

information and a desired quality of service attribute to deliver the multicast information

from a network device for receiving the information, to receive a notification from the

network device that confirms a scheduled delivery of the information from the network

device to an application layer; and to coordinate a power saving protocol of the wireless

communication apparatus to accommodate the scheduled delivery of the information to an

awake state of the wireless communication apparatus based on a multicast schedule; and

a radio frequency (RF) interface operably coupled to the media access controller

(MAC) to transmit and receive the request and the information over an air interface.

18. (Cancelled)

19. (Cancelled)

20. (Cancelled)

SERIAL NO.: 10/812,660 FILED: March 29, 2004

Page 5

21. (Previously Presented) The apparatus of claim 17 wherein the MAC is further configured to send a delete request message requesting removal of the apparatus from the multicast schedule.

- 22. (Previously Presented) The apparatus of claim 17 wherein the apparatus comprises a wireless user station (STA) and a network adaptor.
- 23. (Previously Presented) The apparatus of claim 17 further comprising: at least two antennas coupled to the RF interface.
- 24. (Currently Amended) A wireless communication apparatus comprising: a processing circuit to

receive from [a] two or more client devices application—a request for delivery of information, wherein the request includes a multicast address—an address for the source of information and a quality of service attribute for receiving the information, to—check an existence of said multicast address in a multicast schedule, to update said multicast schedule or to create a new multicast schedule based—on the existence of the multicast address, to coordinate which coordinates the multicast delivery of the information with a power saving protocol of each client device so that the client device will be awake when the multicast delivery of application data packet occurs, to send to the client application a response and to coordinate said power saving protocol to accommodate the scheduled multicast delivery of the information to the client application according to the multicast schedule.

25. (Previously Presented) The apparatus of claim 24 further comprising:

a radio frequency (RF) interface operably coupled to the processing circuit to transmit the information to the client application according to the schedule determined by the processing circuit.

SERIAL NO.: 10/812,660 FILED: March 29, 2004

Page 6

26. (Currently Amended) The apparatus of claim 24 wherein the apparatus comprises a wireless local area network (WLAN) access point complies with an at least Institute of Electrical and Electronic Engineers (IEEE) 802.11(a) and (g) standards.

27. (Cancelled)

28. (Previously Presented) The apparatus of claim 24 wherein the processing circuit is to send the schedule to one or more requesting network devices as a transmission specification (TSPEC) response.

29. (Previously Presented) The apparatus of claim 24 wherein the processing circuit is configured to buffer application data packets for the wireless multicast until a time indicated on the multicast schedule.

30. (Original) The apparatus of claim 25 further comprising:

at least two antennas coupled to the RF interfaces for enabling multiple input multiple output (MIMO) communications.

31. (Currently Amended) A wireless communication system comprising:

a radio frequency (RF) transceiver;

at least two antennas electrically coupled to the RF transceiver; and

a processing circuit electrically coupled with the RF transceiver, wherein the processing circuit is to

receive from [a] two or more client devices application—a request for delivery of information, wherein the request includes includes a multicast address—an address for the source of information and a quality of service attribute for receiving the information, to eheck an existence of said multicast address in a multicast schedule, to update said multicast schedule or to create a new multicast schedule based on the existence of the multicast address, to coordinate which coordinates the multicast delivery of the information with a power saving protocol of each client device so that the client device will be awake when the multicast delivery of application data packet occurs, to send to the client application a

SERIAL NO.:

10/812,660

FILED:

March 29, 2004

Page 7

response and to coordinate said power saving protocol to accommodate the scheduled multicast delivery of the information to the client application and to send the information to the client application according to the multicast schedule.

32. (Cancelled)

33. (Currently Amended) The wireless communication system of claim 31 wherein the requests comprise a transmission specification (TSPEC) complies with an at least Institute of Electrical and Electronic Engineers (IEEE) 802.11 standards including a multicast address and a quality of service (QoS) indicator.

34. (Previously Presented) The wireless communication system of claim 31 wherein the communication system comprises a wireless local area network (WLAN) access point (AP).